

PODÉLNÝ POHLED



CHOONÍK NEBO SCHODIŠTĚ ☐ ROSTLÝ TERČ ☐

	norma	0	12	8,9				
	g/m <sup>2</sup>	0,22	0,395	0,688	7,69			
VÝZUŠNÉ BETONOVÉ LOŽE PRO PALISADY - PRÁVA STRANA SCHOVÍTĚ PRŮ VÝSTUPU NAKOROU								
Pr	Prsmr	Rozm	Rozm	m <sup>2</sup> /ks				
				Kusy	R6	R12	R150	R210
1168	1	0,50,0,5	1				0,50	
2168	3	0,5,1,5	1				1,50	
3168	3	0,5,1,5	1				1,50	
4168	3	0,5,1,5	1				1,50	
5168	3	0,5,1,5	1				1,50	
6168	1,51	0,50,755	1				0,76	
7168	1	0,5,1,5	1				1,00	
8168	3	0,5,1,5	1				1,50	
9168	3	0,5,1,5	1				1,50	
10168	2	0,51	2				2,00	
11168	3	0,5,1,5	1				1,50	
12168	3	0,5,1,5	1				1,00	
13168	3	0,5,1,5	1				1,00	
14168	3	2,0	2	REZERVA			1,00	
				m				20,26
				kg				230,15

Beton C20/25 XC2  
Výztuž SVAŘOVANÉ SÍTĚ KARI  
KRYTÍ SÍTĚ KARI ODE DNA 80MM

[illegible]