

**Tabulka č. 4 - Technická specifikace**

<b>Položka:</b>	<b>Výrobce:</b>	<b>Typ:</b>	<b>Název - popis:</b>	<b>ks</b>
			<b>Artist Intercom</b>	
<b>1.1</b>	<b>Riedel</b>	<b>1082031</b>	<b>VAM Plus Upgrade - 32 to 64</b>	<b>1</b>
			Software upgrade license to transform one VAM-32 Plus license into one VAM-64 Plus license; only one VAM can be linked to an ARTIST-1024 node	
<b>1.2</b>	<b>Riedel</b>	<b>1020100</b>	<b>UIC-128</b>	<b>2</b>
			Software definable input/output card; the UIC-128 can be configured as an SMPTE-2110 30/31 (AES67) IP Layer3, MAD1 or Artist-Fiber interface; it supports up to 128 audio channels; the UIC requires related SFP module/s	
<b>1.3</b>	<b>Riedel</b>	<b>9300645</b>	<b>MN-Z-SFP-1000baseT</b>	<b>4</b>
			CAT5 SFP Modul especially for 1GB / 1000Base-T Ethernet Interfaces; max. approx. 100m cable length with CAT5 cable; 9300645 is replacing 1990017	
			<b>Riedel Bolero</b>	
<b>2.1</b>	<b>Riedel</b>	<b>1430050</b>	<b>BL-BAT-1015-ST</b>	<b>2</b>

			Rechargeable Lithium Ion Battery 17,3 WH for BL-BPK wireless beltpack with charge status telemetry (15hrs plus run-time in BL-BPK beltpack)	
			<b>Intercom panely</b>	
<b>3.1</b>	<b>Riedel</b>	<b>1220120</b>	<b>DSP-2312</b>	<b>3</b>
			Desktop SmartPanel with 12 keys; 2 multi-colored, high-resolution, multi-touch displays; integrated power supply; studio-grade mic preamps; 2 exchangeable XLR connector headset connectors; high-quality loudspeaker; 3 GPI-In; 3 GPI-Out; 1 analog 4-Wire; Matrix link: AES67/AVB and AES3 via license (DSP-2312-LIC-AES3 1220125);SD-Card Slot; 2 USB ports; gooseneck microphone (e.g. MIC-30 6390004) not included; requires matching software application (e.g. RSP-2318-APP-PLUS 1220205)	
<b>3.2</b>	<b>Riedel</b>	<b>1220205</b>	<b>RSP-2318-APP-PLUS</b>	<b>3</b>
			PLUS version of the Intercom Application for RSP-2318 and DSP-2312 SmartPanel; Turns the SmartPanel User Interface into an Intercom Panel; supports 12 keys for Intercom; Individual volume control; Supported connectivity: AES67/AVB, Ethernet; 2 Headsets, 2 USB ports, 1 analog 4-Wire, expansion panel connectivity, option slot, 3 GPI-In, 3 GPI-Out	
<b>3.3</b>	<b>Riedel</b>	<b>1220500</b>	<b>RSP-1232HL</b>	<b>2</b>
			19" / 2RU 1200 series SmartPanel Platform with 32 hybrid lever keys for flexible workflows; 2 full-color, high-resolution, multi-touch key displays; 1 full-color, high-resolution, multi-touch info display; DSP-controlled stereo loudspeakers; 2 SFP and 2 ETH (RJ45) AES67 Matrix Link ports; 2 analog 4-wire connections (RJ45); 3 GPI-In, 3 GPI-Out; 2 headset connectors (XLR/RJ45); 2 Matrix connectors (RJ45/BNC); 2 USB ports; MicroSD card slot; depth: 95 mm / 3.7"; gooseneck microphone (e.g. MIC-30 6390004) not included; requires matching software application (INT_1200_PRO)	

3.4	Riedel	1220600	RSP-1216HL	2
			19" / 1RU 1200 series SmartPanel Platform with 16 hybrid lever keys for flexible workflows; 2 full-color, high-resolution, multi-touch key displays; 1 full-color, high-resolution, multi-touch info display; DSP-controlled loudspeaker; 2 SFP and 2 ETH (RJ45) AES67 Matrix Link ports; 2 analog 4-wire connections (RJ45); 3 GPI-In, 3 GPI-Out; 2 headset connectors (XLR/RJ45); 2 Matrix connectors (RJ45/BNC); 2 USB ports; MicroSD card slot; depth: 95 mm / 3.7"; gooseneck microphone (e.g. MIC-30 6390004) not included; requires matching software application (INT_1200_PRO)	
3.5	Riedel	1220250	INT_1200_PRO	4
			PRO version of the Intercom Application for the RSP-1232HL / RSP-1216HL SmartPanels; turns the RSP-1232HL / RSP-1216 HL User Interfaces into Intercom Panels; supports 32 (resp. 16) keys; 2 SFP and 2 ETH (RJ45) AES67 Matrix Link ports; 2 analog 4-wire connections (RJ45); 3 GPI-In, 3 GPI-Out; 2 headset connectors (XLR/RJ45); 2 Matrix connectors (RJ45/BNC); 2 USB ports; SMPTE ST2022-7	
3.6	Riedel	6390004	MIC-30	8
			Electret microphone for Intercom/Performer panels  cardioid  length: 30cm	
3.7	Riedel	1220700	ESP-1216HL	1
			19" / 1RU 1200 series Expansion SmartPanel with 16 hybrid lever keys for flexible workflows; 2 full-color, high-resolution, multi-touch key displays; 2 expansion I/O connectors for daisy-chaining up to 6 expansion panels on one RSP-1216HL or RSP-1232HL; depth: 95 mm / 3.7"	
3.8	Riedel	1010006	PSU-032	1

			Power supply for Artist mainframe MFR-032 G2; two units are required per mainframe for PSU redundancy	
			<b>Rozšíření VoIP</b>	
4.1	Cisco	P-5GS6-GL=	5G Sub-6 GHz Pluggable Interface Module (PIM) for C8K only	2
4.2	Cisco	SL-1100-4P-SEC=	Security License for Cisco ISR 1100 4P Series	3
4.3	Cisco	C1131-8PLTEPWE	Cisco Gigabit Ethernet security router	2
			<b>Ostatní</b>	
5.1	SI	install	upgrade systému na nejnovější verzi	1
5.2	SHIP	Shipping		1