

SPODNÍ STUPEŇ ZÁKLADOVÉHO PASU; M1:50




## M1:50





## 1:25



## M1:25



## M1:25



		VÝKAZ PO PRŮZŘECH		
	PRŮZŘ (mm)			
	H150	146,2	51,30	7500,
	P15	2,125	117,75	250,
	KANSTIS 8/150/150	498,3	5,40	2690,
	6	310,4	0,22	68,
	8	2464,0	0,39	948,
	10	552,64	0,62	340,
	12	1485,03	0,89	1318,
	14	929,72	1,21	1123,
	20	135,64	2,47	334,
	22	60,08	2,98	179,
	<b>CEKEM</b>			<b>14755,</b>
	Kontrola			0,0
	Reverze 5%			737,
	<b>CEKEM</b>			<b>15492,</b>

VÝZTUŽ  $\phi$  6 mm - minimálně  $\phi$  24 mm



Kotevní a stykové délky pro jednotlivé výztuže se určí individuálně dle ČSN EN

BETON MUSÍ BÝT DLE ČSN EN 206+A2 A ČSN P 73 240

BETON MUSÍ BÝT DLE ČSN EN 206+A2 A ČSN P 73 240

BETON: C30/37 XC2 XF2 XA1; CI 0,2; Dmax 22; S3

[illegible]