



PHASE		DESCRIPTION					
1		OPEN THE DOOR					
2		INSERT TABLES ON REINFORCEMENT (TO BE USED AS A SUPPORT)					
3		REMOVE THE FIRST CENTER ROW OF FILTRATION CARTRIDGES, TO EASILY ENTER INTO THE FILTER					
4		TO RELEASE THE CARTRIDGES, UNSCREW THE M8 NUT AT THE BASE, LIFT THE CARTRIDGES AND THE INTERNAL ROD, TILT THE ROD FOR EASY RELEASE					
5		REMOVE THE SCREW AND THE WASHER, THAN REMOVE THE ROD FROM BOTTOM UP					
6		GET A NEW CARTRIDGES, INSERT THE ROD FROM TOP TO BOTTOM, THAN SCREW THE NUT AND THE WASHER (BE CAREFUL NOT TO SCREW TIGHT THE NUT, THE ROD MUST SLIDE INTO THE CARTRIDGES)					
7		PLACE THE CARTRIDGES AND THE ROD INTO THE FILTER, UNDER THE HOOK, THAN SLIDE THE ROD UPWARDS, TILT IT AND HOOK IT TO THE UPPER EYELET, SECURE THE ROD AND SCREW TIGHT THE INFERIOR NUT					
			COD. CLIENTE	CLIENTE	COMMESSA	DATE	
						13/06/2025	
DIS. REDATTO DA D. PISCITELLI	CONTROLLATO DA A. TOCCACELI	APPROVATO DA A. TOCCACELI	OPERATORE	FASE LAVORAZ.	ORE	MINUTI	
				DISEGNO			
				NESTING			
				TAGLIO			
TOT. KG.		CONSEGNA PER IL		PIEGA			
979.26				ASSEMBLAGGIO			
				VERNICIATURA			
OBJECT			SCALA	DRAWING			
FILTRO N°42 CARTUCCE D.220 H.1000 CON SISTEMA DI PULIZIA A LAVAGGIO CON ARIA COMP. 2440X4187,99 H.4187,99				1:15	1FLNP2PC1002204201		