

SEZNAM PAŽNIC V POŘADÍ ZAPOUSTĚNÍ

TEŽEBNÍ

kolony 6

7"

na vrstvě

DUNAJOVICE 29

pořadové číslo	materiál druh	síla stěny mm	délka pažnice	nedo- brub. kolony	celková délka	poznámka
			0,55			DATA
①	J 55	9,19	11,10		11,65	FS ^v
			0,68		12,33	ZU
②	J 55	9,19	11,23		23,56	
	↑	9,19	3,42		26,98	REFEEL 7"
③		↑	11,67		38,65	
④			11,08		49,73	FS ^v
⑤			10,80		60,53	
⑥			11,18		71,71	
⑦			10,69		82,40	FS ^v
⑧			11,30		93,70	
⑨			10,61		104,31	
⑩			11,11		115,42	FS ^v
⑪			11,09		126,51	
⑫			10,81		137,32	
⑬			10,86		148,18	FS ^v
⑭			10,99		159,17	
⑮			11,04		170,21	
⑯			10,81		181,02	FS ^v
⑰			10,87		191,89	
⑱			11,27		203,16	
⑲			11,31		214,47	FS ^v
⑳			12,03		226,50	
㉑			11,45		237,95	
㉒			10,71		248,66	FS ^v
㉓			11,30		259,96	
㉔			10,93		270,89	
㉕			11,14		282,03	FS ^v
㉖			10,55		292,58	
㉗			11,16		303,74	
㉘			10,79		314,53	FS ^v
㉙	↓	↓	10,86		325,39	
㉚	J 55	9,19	11,15		336,54	

F - FONAL

Ž - ŽELEZA

7822-6112

SEZNAM PAŽNIC V POŘADÍ ZAPOČÍTÁNÍ

TĚŽEBNÍ

kolony 6

71

na vrstvě

DUNAJOVICE 29

pořadové číslo	materiál druh	síla stěny mm	délka pažnice	pod- řad. č.	celková délka kolony	poznámka
(31)	J 55	9,19	10,56		347,10	F ^u
(32)	↑	↑	11,40		358,50	
(33)			11,02		369,52	
(34)			11,12		380,64	F ^u
(35)			11,55		392,19	
(36)			10,75		402,94	
(37)			11,48		414,42	F ^u
(38)			11,09		425,51	
(39)			10,84		436,35	
(40)			10,91		447,26	F ^u
(41)			10,92		458,18	
(42)			10,82		469,00	
(43)			10,55		479,55	F ^u
(44)			11,20		490,75	
(45)			10,27		501,02	
(46)			11,15		512,17	F
(47)			11,08		523,25	
(48)			10,71		533,96	
(49)			10,64		544,60	F
(50)			10,71		555,31	
(51)			11,01		566,32	
(52)			11,02		577,34	F
(53)			10,97		588,31	
(54)			11,11		599,42	
(55)			11,15		610,57	F
(56)			11,21		621,78	
(57)			10,60		632,38	
(58)			11,59		643,97	F
(59)			11,07		655,04	
(60)			11,22		666,26	
(61)			11,33		677,59	F
(62)	↓	↓	10,98		688,57	
(63)	J 55	9,19	11,47		700,04	

TEŽEBNÍ

kolony s

7'

na vrtbě

DUNAJOVICE 29

pořadové číslo	materiál druh	síla stěny mm	délka pažnice	pod- šrub. díř.	celková délka kolony	poznámka
(64)			11,52		711,56	
(65)			11,10		722,66	F
(66)			10,88		733,54	
(67)			11,22		744,76	
(68)			11,44		756,20	F
(69)			11,06		767,26	
(70)			11,33		778,59	" F
(71)			11,36		789,95	"
(72)			10,96		800,91	
(73)			10,99		811,90	F
(74)			10,82		822,72	
(75)			10,89		833,61	
(76)			10,91		844,52	F
(77)			10,66		855,18	
(78)			10,99		866,17	
(79)			11,30		877,47	F
(80)			12,07		889,54	
(81)			11,17		900,71	
(82)			10,83		911,54	F
(83)			11,20		922,74	
(84)			11,33		934,07	
(85)			11,20		945,27	F
(86)			10,88		956,15	
(87)			10,80		966,95	
(88)			10,96		977,91	F
(89)			10,76		988,67	
(90)			12,02		1.000,69	
(91)			10,75		1.011,44	F
(92)			10,81		1.022,25	
(93)			11,91		1.033,36	F
(94)			11,90		1.045,26	F
			3,13		1.048,39	BEPER
					3,50	STĚL + ELEVÁTOR

1.044,89m

Zlamy
3.9.87

2282-2282